



## SUPRASKIN AUTOMATIC SKIN PACKAGING MACHINE

Easy-operation automatic machine for skin-type packing. Useful area of 500 x 700 mm (19 1/2" x 27 1/2"). Supraskin was designed specifically to perform skin-type packaging. It is not a vacuum forming machine adapted to such purpose.



### TECHNICAL SPECIFICATIONS

Output.....	60-80 cycles per hour
Plastic grade.....	PVC, Surlyn™ ( Du Pont )
Plastic thickness.....	0.05 to 0.6 mm (0.0002'' to 0.025'')
Molding area.....	300 x 700 mm (19 1/2'' x 27 1/2'')
Film width .....	750 mm (29 1/2'')
Maximum molding height.....	140 mm (5 1/2'')
Weight.....	300 Kg
Dimensions (m).....	1,0L x 1,62W x 1,56H (39 1/2''x 64''x 61 1/2'')
Oven power.....	12 Kw
Motor power.....	3 HP
Electrical consumption.....	4 Kw

Samples:



General specifications:

- It works with PVC or Surlyn ( Du Pont <sup>TM</sup>)
- Resistances of low thermal inertia allow the machine to be turned on at each cycle with no waste of energy
- The high temperature of the resistances (until they get red) causes a high transmission of infrared waves to the card ensuring a perfect sealing between the plastic and the card.
- Stainless-steel furnace prevents oxidation caused by chloride molecules of PVC.
- All movements are automatic and do not require compressed air.
- The cooling process uses cooling fan and vacuum system at the same time to minimize the problem of distortion caused by shrinking of the plastic film.
- Plastic is inserted into the machine from its rear. This allows the operator to prepare the new products to be packed on a table located at the side of the machine at the same time that the machine is working.
- Equipped with plastic cutting device.
- Full one-year warranty for all its components



Eletro-Forming Equipamentos para Embalagens, Ltda  
Rua C. C. Oliveira, 280  
Embú – SP – Brasil  
Phone : 55 11 4704-3699  
Fax : 55 11 4704-3987  
Site : [www.eletro-forming.com](http://www.eletro-forming.com)  
E-mail : [info@eletro-forming.com](mailto:info@eletro-forming.com)